

# FLOS

■ F6499030 Black

## String Light - Cone head - 22mt cable - CASAMBI Ready

Designed by Michael Anastassiades, 2014




21W - 1035lm - 2700K

Suspension lamp providing diffused light. Black, white or blue varnished die-cast aluminium body coated with clear soft-touch varnish. Optical diffuser in opal PC. Suspension system of 22 metres with Kevlar reinforced coaxial cable. Available with wall/ceiling connection in black PC and power supply with floor switch in black varnished PC. The on/off switch is electronic with optical and touch dimm mechanism included or touch dimm and CASAMBI Ready version. Dimmer included. Compulsory to add either floor switch or ceiling/wall rose.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

EAN	8059607042298
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
LED type	LED array
Power (W)	21
System flux (lm)	1035

### Physical

Colour	Black
Length (mm)	190
Cord length (mm)	22000
Net weight (kg)	1.15
Package height (mm)	300
Package width (mm)	300
Package length (mm)	300
Package volume (m3)	0.03
IP internal	20

### Download

Mounting instructions	↓ PDF
Mounting instructions	↓ PDF
Mounting instructions	↓ PDF
Spare Parts	↓ PDF

### Photometric Files


LDT / IES	↓ LDT
-----------	-------

### Technical Drawings

🔒 Bim	↓ ZIP
-------	-------



## Schematic light drawing



Luminous flux Luminaire  
1035 lm

## Photometric

Lighting type	Direct
Light distribution	Roto symmetric
CCT (K)	2700

## Electrical

Insulation class	III
Main voltage (Vac)	48
Forward voltage (V)	48
LED voltage Vf (Vdc)	null
Driver	Remote excluded
Dimmable	Yes
Dimming type	Electronic 48V
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only)  
light source by a  
professional

## Accessories & Power Supply



REQUIRED

F6482030


String Light Rose



REQUIRED

F6484030

String Light Floor switch



OPTIONAL

F6485030

String Light Kit cable

## Spare Parts



- |     |   |           |
|-----|---|-----------|
| 01. | Kit with white hooks and white cable clamps             | RF6480109 |
| 01. | String Light black hooks & cable clamps 5-unit kit      | RF6480130 |
| 02. | Power supply unit for led                               | RF22934   |
| 03. | Kit with allen key and screws for ceiling rose assembly | RF6480200 |
| 03. | Kit with allen key and screws for ceiling rose assembly | RFU648200 |

**DOWNLOAD**



RF6480109

Kit with white hooks and white cable clamps



RF6480130

String Light black hooks & cable clamps 5-unit kit




RF22934

Power supply unit for led



RF6480200

Kit with allen key and screws for ceiling rose assembly



RFU648200

Kit with allen key and screws for ceiling rose assembly

# FLOS

F6498014 Blue

## String Light - Sphere head - 22mt cable - CASAMBI Ready

Designed by Michael Anastassiades, 2014




21W - 1515lm - 2700K

Suspension lamp providing diffused light. Black, white or blue varnished die-cast aluminium body coated with clear soft-touch varnish. Optical diffuser in opal PC. Suspension system of 22 metres with Kevlar reinforced coaxial cable. Available with wall/ceiling connection in black PC and power supply with floor switch in black varnished PC. The on/off switch is electronic with optical and touch dimm mechanism included or touch dimm and CASAMBI Ready version. Dimmer included. Compulsory to add either floor switch or ceiling/wall rose.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

EAN	8059607042304
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
LED type	LED array
Power (W)	21
System flux (lm)	1515

### Physical

Colour	Blue
Length (mm)	190
Cord length (mm)	22000
Net weight (kg)	1.27
Package height (mm)	300
Package width (mm)	300
Package length (mm)	300
Package volume (m3)	0.03
IP internal	20

### Download

Mounting instructions	↓ PDF
Mounting instructions	↓ PDF
Mounting instructions	↓ PDF
Spare Parts	↓ PDF

### Photometric Files


LDT / IES	↓ LDT
-----------	-------

### Technical Drawings

🔒 Bim	↓ ZIP
-------	-------




## Schematic light drawing



## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only)  
light source by a  
professional

## Photometric

Lighting type	Total
Light distribution	Roto symmetric
CCT (K)	2700

## Electrical

Insulation class	III
Main voltage (Vac)	48
Forward voltage (V)	48
LED voltage Vf (Vdc)	null
Driver	Remote excluded
Dimming type	Electronic 48V
Batteries inside	No

## Accessories & Power Supply



REQUIRED

F6482014

String Light Canopy in Blue



REQUIRED

F6484014

Sting Light Floor Switch



REQUIRED

F6484314

Sting Light Floor Switch



OPTIONAL

F6485014

String Light Cable



## Spare Parts



- |     |   |           |
|-----|---|-----------|
| 01. | Kit with white hooks and white cable clamps             | RF6480109 |
| 01. | Kit with Blue Hooks and Blue Wire Clamps                | RF6480114 |
| 02. | Power supply unit for led                               | RF22934   |
| 03. | Kit with allen key and screws for ceiling rose assembly | RF6480200 |
| 03. | Kit with allen key and screws for ceiling rose assembly | RFU648200 |

**DOWNLOAD**



RF6480109  
Kit with white hooks and white cable clamps




RF6480114  
Kit with Blue Hooks and Blue Wire CLamps



RF22934  
Power supply unit for led



RF6480200  
Kit with allen key and screws for ceiling rose assembly



RFU648200  
Kit with allen key and screws for ceiling rose assembly