


Cosmos

Design by Lievore, Altherr, Molina


Design and light become one with Cosmos pendant. Flattened spheres in suspension that naturally descend from the ceiling and use light to draw a fluctuating course like a constellation of stars.

Pendant



Ø 19 cm

2500



Ø 27 cm

2501



Ø 48 cm

2502



55 cm

2510



65 cm

2511



76 cm


2515



86 cm

2516

2500



Finishes

- **14/** _ _ Chocolate (RAL 8019)
- **62/** _ _ Green (PANTONE 5645)
- **58/** _ _ Off-White (NCS S 2005-Y20R)

LED Colour Temperature

- /1** _ 2700 K - 485 lm CRI >90
- /3** _ 3500 K - 128 lm CRI >80

Control

- 2500** _ _ / _ _
-
- _ _ / _ **0** On/ Off
- _ _ / _ **1** DALI-2
-
- _ _ / _ **Z** Casambi

Materials

Diffuser: PC- Polycarbonate.
Body: PU- Polyurethane.
Canopy: Steel.

Light Source and electronics

1 x LED 4,5 W 350mA
Constant Current 350 mA
/ 10: 100-240V 50/60Hz
/ 1B: 110-240V 50/60Hz

Packaging


1 Box 0,26 x 0,26 x 0,26 m
Vol 0,0180 m³
Gross weight 1,62 Kg Net weight 1,18 Kg

Notes

Extra cable length.



2501



- Finishes**
- **14/** _ _ Chocolate (RAL 8019)
 - **62/** _ _ Green (PANTONE 5645)
 - **58/** _ _ Off-White (NCS S 2005-Y20R)

LED Colour Temperature

/1 _ 2700 K - 485 lm
CRI >90

/3 _ 3500 K - 512 lm
CRI >80

E →

Control

2501 _ _ / _ _

_ _ / _ **0** On/ Off

_ _ / _ **1** DALI-2

_ _ / _ **Z** Casambi

Materials

Diffuser: PC- Polycarbonate.
Body: PU- Polyurethane.
Canopy: Steel

Light Source and electronics

1 x LED 4,5 W 350mA
Constant Current 350 mA
/ **10**: 100-240V 50/60Hz
/ **1B**: 110-240V 50/60Hz

Packaging


1 Box 0,42 x 0,42 x 0,25 m
Vol 0,0441 m³
Gross weight 2,54 Kg Net weight 1,44 Kg

Notes

Extra cable length.

LED IP20 CE UK ENEC Bi-volt

2502



- Finishes**
- **10/** _ _ White (NCS S 0300-N)

LED Colour Temperature

/1 _ 2700 K - 485 lm
CRI >90

/3 _ 3500 K - 512 lm
CRI >80

E →

Control

2502 _ _ / _ _

_ _ / _ **0** On/ Off

_ _ / _ **1** DALI-2

_ _ / _ **Z** Casambi

Materials

Diffuser: PC- Polycarbonate.
Body: PU- Polyurethane.
Canopy: Steel.

Light Source and electronics

1 x LED 4,5 W 350 mA.
1 x LED 1 W 350 mA.
Constant Current 350 mA
110-240V 50/60Hz

Packaging


1 Box 0,60 x 0,60 x 0,27 m
Vol 0,0970 m³
Gross weight 5,58 Kg Net weight 3,15 Kg

Notes

Extra cable length.

LED IP20 CE UK ENEC Bi-volt

2510



- Finishes**
- **62/** _ _ Green, White and Chocolate (PANTONE 5645, NCS S 0300-N, RAL 8019)

LED Colour Temperature

/1 _ 2700 K - 1455 lm
CRI >90

/2 _ 3500 K - 1537 lm
CRI >80

E →

Control

2510 _ _ / _ _

_ _ / _ **A** Push; 1-10V; DALI-2

_ _ / _ **Z** Casambi

Materials

Diffuser: PC- Polycarbonate.
Body: PU- Polyurethane.
Canopy: Steel.

Light Source and electronics

3 x LED 4,5 W 350 mA
Constant Current 350 mA
110-240V 50/60Hz

Packaging

1 Box 0,60 x 0,60 x 0,27 m
Vol 0,0970 m³
Gross weight 7,54 Kg Net weight 5,11 Kg

Notes

Compositions and finishes can not be changed
Extra cable length.

LED IP20 CE UK ENEC Bi-volt

<p>2511</p>	<p>Finishes</p> <ul style="list-style-type: none"> 62/ __ Green, White and Chocolate (PANTONE 5645, NCS S 0300-N, RAL 8019) 58/ __ Off-White, White and Chocolate (NCS S 2005-Y20R, NCS S 0300-N, RAL 801) 	<p>LED Colour Temperature</p> <p>/1 _ 2700 K - 1455 lm CRI >90</p> <p>/3 _ 3500 K - 1537 lm CRI >80</p> <p>E →</p>	<p>Control</p> <p>2511 __ / __</p> <p>__ / _ A Push; 1-10V; DALI-2</p> <p>__ / _ Z Casambi</p>
	<p>Materials</p> <p>Diffuser: PC- Polycarbonate. Body: PU- Polyurethane. Canopy: Steel.</p> <p>Light Source and electronics</p> <p>3 x LED 4,5 W 350 mA 1 x LED 1 W 350 mA. Constant Current 350 mA 110-240V 50/60Hz</p>	<p>Packaging</p> <p>1 Box 0,60 x 0,60 x 0,27 m Vol 0,0970 m³ Gross weight 9,25 Kg Net weight 6,82 Kg</p> <p>Notes</p> <p>Compositions and finishes can not be changed Extra cable length.</p> <p>LED IP20 Bi-volt</p>	

<p>2515</p>	<p>Finishes</p> <ul style="list-style-type: none"> 62/ __ Green, Chocolate and Off-White (Pantone 5645, RAL 8019, NCS S 2005-Y20R) 	<p>LED Colour Temperature</p> <p>/1 _ 2700 K - 1940 lm CRI >90</p> <p>/3 _ 3500 K - 2050 lm CRI >80</p> <p>E →</p>	<p>Control</p> <p>2515 __ / __</p> <p>__ / _ A Push; 1-10V; DALI-2</p> <p>__ / _ Z Casambi</p>
	<p>Materials</p> <p>Diffuser: PC- Polycarbonate. Body: PU- Polyurethane. Canopy: Steel.</p> <p>Light Source and electronics</p> <p>4 x LED 4,5 W 350 mA Constant Current 350 mA 110-240V 50/60Hz</p>	<p>Packaging</p> <p>1 Box 0,76 x 0,76 x 0,27 m Vol 0,1560 m³ Gross weight 10,94 Kg Net weight 7,04 Kg</p> <p>Notes</p> <p>Compositions and finishes can not be changed Extra cable length.</p> <p>LED IP20 Bi-volt</p>	

<p>2516</p>	<p>Finishes</p> <ul style="list-style-type: none"> 62/ __ Green, White and Chocolate (PANTONE 5645, RAL 9010, RAL 8019) 	<p>LED Colour Temperature</p> <p>/1 _ 2700 K - 1940 lm CRI >90</p> <p>/3 _ 3500 K - 2050 lm CRI >80</p> <p>E →</p>	<p>Control</p> <p>2516 __ / __</p> <p>__ / _ A Push; 1-10V; DALI-2</p> <p>__ / _ Z Casambi</p>
	<p>Materials</p> <p>Diffuser: PC- Polycarbonate. Body: PU- Polyurethane. Canopy: Steel.</p> <p>Light Source and electronics</p> <p>4 x LED 4,5 W 350 mA 2x LED 1 W 350 mA Constant Current 350 mA 110-240V 50/60Hz</p>	<p>Packaging</p> <p>1 Box 0,73x0,73x0,32 m Vol 0,1705 m³ Gross weight 14,62 Kg Net weight 15,5 Kg</p> <p>Notes</p> <p>Compositions and finishes can not be changed Extra cable length.</p> <p>LED IP20 Bi-volt</p>	

