

Pendant

3720



Ø 25 cm

3724



Ø 25 cm

3726



Ø 25 cm

3728



Ø 25 cm

3730



Ø 25 cm

3734



150 cm

3735



150 cm

3736



195 cm


3720

Finishes  
 ● 18/ \_\_ Graphite  
 (ADAPTA RF 9913 WX)

LED Colour Temperature  
 /1\_ 2700 K - 868 lm  
 F  
 CRI >90

Control

3720 \_\_ / \_\_  
 \_\_ / 11 DALI-2  
 \_\_ / 1B Push; 1-10V  
 \_\_ / 1Z Casambi



Materials

Diffuser: Blown-glass.  
 Profile: Aluminum.

Light Source and electronics

2 x LED 4,6 W 500 mA  
 Constant Current 500 mA  
 110-240V 50/60Hz

Packaging


1 Box 0,71 x 0,27 x 0,21 m  
 Vol 0,0413 m<sup>3</sup>  
 Gross weight 3,75 Kg Net weight 2,8 Kg

Notes

Extra cable length.

LED IP20 CE UK ENE Bi-volt

3724



Finishes  
 ● 18/ \_ \_ Graphite  
 (ADAPTA RF 9913 WX)

LED Colour Temperature  
 /1\_ 2700 K - 868 lm  
 F  
 CRI >90

Control

3724 \_ \_ / \_ \_  
 \_ \_ / 11 DALI-2  
 \_ \_ / 1B Push; 1-10V  
 \_ \_ / 1Z Casambi


Materials  
 Diffuser: Blown-glass.  
 Profile: Aluminum.  
 Planter: PMMA.

Light Source and electronics  
 2 x LED 4,6 W 500 mA  
 Constant Current 500 mA  
 110~240V 50/60Hz

Packaging  
 1 Box 1,02 x 0,27 x 0,21 m  
 Vol 0,0588 m<sup>3</sup>  
 Gross weight 4,6 Kg Net weight 3,3 Kg

Notes  
 Extra cable length.  
 LED IP20 CE UK ENEC ENEC Bi-volt

3726



Finishes  
 ● 18/ \_ \_ Graphite  
 (ADAPTA RF 9913 WX)

LED Colour Temperature  
 /1\_ 2700 K - 1736 lm  
 F  
 CRI >90

Control

3726 \_ \_ / \_ \_  
 \_ \_ / 11 DALI-2  
 \_ \_ / 1B Push; 1-10V  
 \_ \_ / 1Z Casambi


Materials  
 Diffuser: Blown-glass.  
 Profile: Aluminum.

Light Source and electronics  
 4 x LED 4,6 W 500 mA  
 Constant Current 500 mA  
 110~240V 50/60Hz

Packaging  
 1 Box 1,02 x 0,27 x 0,21 m  
 Vol 0,0588 m<sup>3</sup>  
 Gross weight 5,4 Kg Net weight 4,1 Kg

Notes  
 Extra cable length.  
 LED IP20 CE UK ENEC ENEC Bi-volt

3728



Finishes  
 ● 18/ \_ \_ Graphite  
 (ADAPTA RF 9913 WX)

LED Colour Temperature  
 /1\_ 2700 K - 1736 lm  
 F  
 CRI >90

Control

3728 \_ \_ / \_ \_  
 \_ \_ / 11 DALI-2  
 \_ \_ / 1B Push; 1-10V  
 \_ \_ / 1Z Casambi


Materials  
 Diffuser: Blown-glass.  
 Profile: Aluminum.  
 Planter: PMMA.

Light Source and electronics  
 4 x LED 4,6 W 500 mA  
 Constant Current 500 mA  
 110~240V 50/60Hz

Packaging  
 1 Box 0,75 x 0,53 x 0,21 m  
 Vol 0,0857 m<sup>3</sup>  
 Gross weight 8,8 Kg Net weight 4,7 Kg

Notes  
 Extra cable length.  
 LED IP20 CE UK ENEC ENEC Bi-volt

3730



Finishes  
 ● 18/ \_ \_ Graphite  
 (ADAPTA RF 9913 WX)

LED Colour Temperature  
 /1 \_ 2700 K - 2604 lm  
 F  
 CRI >90

Control  
 3730 \_ \_ / \_ \_

\_ \_ / 1A Push; 1-10V; DALI-2  
 \_ \_ / 1Z Casambi

Materials

Diffuser: Blown-glass.  
 Profile: Aluminum.

Light Source and electronics  
 6 x LED 4,6 W 500 mA  
 Constant Current 500 mA  
 110-240V 50/60Hz

Packaging


1 Box 0,75 x 0,53 x 0,21 m  
 Vol 0,0857 m<sup>3</sup>  
 Gross weight 9,5 Kg Net weight 5,4 Kg

Notes

Extra cable length.



3734



Finishes  
 ● 18/ \_ \_ Graphite  
 (ADAPTA RF 9913 WX)

LED Colour Temperature  
 /1 \_ 2700 K - 2265 lm  
 F  
 CRI >90

Control  
 3734 \_ \_ / \_ \_

\_ \_ / 1A Push; 1-10V; DALI-2  
 \_ \_ / 1Z Casambi

Materials

Diffuser: Blown-glass.  
 Profile: Aluminum.  
 Planter: PMMA.

Light Source and electronics  
 1 x LED 2 W 500 mA  
 4 x LED 4,6 W 500 mA  
 Constant Current 500 mA  
 110-240V 50/60Hz

Packaging


1 Box 1,72 x 0,33 x 0,31 m  
 Vol 0,1790 m<sup>3</sup>  
 Gross weight 9,4 Kg Net weight 5,95 Kg

Notes

Extra cable length.



3735



Finishes  
 ● 18/ \_ \_ Graphite  
 (ADAPTA RF 9913 WX)

LED Colour Temperature  
 /1 \_ 2700 K - 2265 lm  
 F  
 CRI >90

Control  
 3735 \_ \_ / \_ \_

\_ \_ / 1A Push; 1-10V; DALI-2  
 \_ \_ / 1Z Casambi

Materials

Diffuser: Blown-glass.  
 Profile: Aluminum.

Light Source and electronics  
 6 x LED 4,6 W 500 mA  
 Constant Current 500 mA  
 110-240V 50/60Hz

Packaging


1 Box 1,72 x 0,33 x 0,31 m  
 Vol 0,1790 m<sup>3</sup>  
 Gross weight 9,4 Kg Net weight 5,95 Kg

Notes

Extra cable length.



3736



Finishes  
 ● 18/ \_ \_ Graphite  
 (ADAPTA RF 9913 WX)

LED Colour Temperature  
 /1 \_ 2700 K - 3133 lm  
 F  
 CRI >90

Control  
 3736 \_ \_ / \_ \_

\_ \_ / 1A Push; 1-10V; DALI-2  
 \_ \_ / 1Z Casambi

Materials

Diffuser: Blown-glass.  
 Profile: Aluminum.  
 Planter: PMMA.

Light Source and electronics  
 1 x LED 2 W 500 mA  
 6 x LED 4,6 W 500 mA  
 Constant Current 500 mA  
 110-240V 50/60Hz

Packaging

1 Box 2,17 x 0,33 x 0,31 m  
 Vol 0,2219 m<sup>3</sup>  
 Gross weight 12,29 Kg Net weight 8,16 Kg

Notes

Extra cable length.

