

# Duo

Design by Ramos & Bassols

Duo brings natural warmth to a space. Its gently curved form encases a supple wood-finished interior, lending a soothing sensibility.

## Ceiling

4870

Ø 47,5 cm



4872

Ø 78,5 cm



4874

Ø 35 cm



4878

Ø 70 cm



4876

Ø 35 cm



4880

Ø 70 cm



4870

### Finishes

- 18/ \_\_ Graphite (Adapta RF9913WX)
- 58/ \_\_ Cream (RAL 7044)
- 93/ \_\_ White (RAL 9016)

Finish customization (Available options: Vibia colour palette. Minimum quantity 10 units. Price + 10%)

### Materials

Diffuser: PC- Polycarbonate.  
Main Body: Aluminum.  
Inner structure: Oak wood.

### Light Source and electronics

1 x LED PLATE 26,5 W 700 mA  
Constant Current 700 mA  
110-240V 50/60Hz

### LED Colour Temperature

**Static White**  
/1 \_ 2700 K - 2207 lm  
/3 \_ 3500 K - 2304 lm  
F →

**Tunable White**  
/8 \_ (2200 K - 4000 K)  
1901 lm - 2461 lm  
G → - F →  
CRI >90

### Control

4870 \_\_ / \_\_


\_\_ / \_ A Static White +  
Push; 1-10V; DALI-2  
\_\_ / \_ Z Static White +  
Casambi

\_\_ / \_ 81 Tunable White +  
DALI-2 DT8  
\_\_ / \_ 8Z Tunable White +  
Casambi


### Packaging

1 Box 0,56 x 0,56 x 0,26 m  
Vol 0,0815 m<sup>3</sup>  
Gross weight 7 Kg Net weight 6 Kg

LED IP20 CE ENEC ENEC Bi-volt



4872



**Finishes**  
 ● 18/ \_\_ Graphite (Adapta RF9913WX)  
 ● 58/ \_\_ Cream (RAL 7044)  
 ● 93/ \_\_ White (RAL 9016)  
**Finish customization**  
 (Available options: Vibia colour palette. Minimum quantity 10 units. Price + 10%)

**LED Colour Temperature**  
**Static White**  
 /1 \_ 2700 K - 3959 lm  
 [F] →  
 /3 \_ 3500 K - 4133 lm  
 [E] →  
**Tunable White**  
 /8 \_ (2200 K - 4000 K)  
 3138 lm - 4238 lm  
 [G] → - [F] →  
 CRI >90

**Control**  
**4872** \_\_ / \_\_  
 \_\_ / \_ A Static White + Push; 1-10V; DALI-2  
 \_\_ / \_ Z Static White + Casambi  
 \_\_ / \_ 81 Tunable White + DALI-2 DT8  
 \_\_ / \_ 8Z Tunable White + Casambi


**Materials**  
 Diffuser: PC- Polycarbonate.  
 Main Body: Aluminum.  
 Inner structure: Oak wood.

**Light Source and electronics**  
 1 x LED PLATE 50 W 700 mA  
 Constant Current 750 mA  
 110-240V 50/60Hz

**Packaging**  
 1 Box 0,9 x 0,9 x 0,25 m  
 Vol 0,2025 m<sup>3</sup>  
 Gross weight 19 Kg Net weight 17 Kg



4874



**Finishes**  
 ● 18/ \_\_ Graphite (Adapta RF9913WX)  
 ● 58/ \_\_ Cream (RAL 7044)  
 ● 93/ \_\_ White (RAL 9016)  
**Finish customization**  
 (Available options: Vibia colour palette. Minimum quantity 10 units. Price + 10%)

**LED Colour Temperature**  
**Static White**  
 /1 \_ 2700 K - 644 lm  
 /3 \_ 3500 K - 632 lm  
 [G] →  
**Tunable White**  
 /8 \_ (2200 K - 4000 K)  
 1244 lm - 1582 lm  
 [G] → - [F] →  
 CRI >90

**Control**  
**4874** \_\_ / \_\_  
 \_\_ / \_ 1 Static White + DALI-2  
 \_\_ / \_ B Static White + Push; 1-10V  
 \_\_ / \_ Z Static White + Casambi  
 \_\_ / \_ 81 Tunable White + DALI-2 DT8  
 \_\_ / \_ 8Z Tunable White + Casambi


**Materials**  
 Diffuser: PC- Polycarbonate.  
 Main Body: Aluminum.  
 Inner structure: Oak wood.

**Light Source and electronics**  
 1 x LED PLATE 12 W 350 mA  
 Constant Current 350 mA  
 110-240V 50/60Hz

**Packaging**  
 1 Box 0,44 x 0,44 x 0,35 m  
 Vol 0,0678 m<sup>3</sup>  
 Gross weight 5 Kg Net weight 4 Kg



4876



**Finishes**  
 ● 18/ \_\_ Graphite (Adapta RF9913WX)  
 ● 58/ \_\_ Cream (RAL 7044)  
 ● 93/ \_\_ White (RAL 9016)  
**Finish customization**  
 (Available options: Vibia colour palette. Minimum quantity 10 units. Price + 10%)

**LED Colour Temperature**  
**Static White**  
 /1 \_ 2700 K - 644 lm  
 /3 \_ 3500 K - 632 lm  
 [G] →  
**Tunable White**  
 /8 \_ (2200 K - 4000 K)  
 1244 lm - 1582 lm  
 [G] → - [F] →  
 CRI >90

**Control**  
**4876** \_\_ / \_\_  
 \_\_ / \_ 1 Static White + DALI-2  
 \_\_ / \_ B Static White + Push; 1-10V  
 \_\_ / \_ Z Static White + Casambi  
 \_\_ / \_ 81 Tunable White + DALI-2 DT8  
 \_\_ / \_ 8Z Tunable White + Casambi


**Materials**  
 Diffuser: PC- Polycarbonate.  
 Main Body: Aluminum.  
 Inner structure: Oak wood.

**Light Source and electronics**  
 1 x LED PLATE 12 W 350 mA  
 Constant Current 350 mA  
 110-240V 50/60Hz

**Packaging**  
 1 Box 0,44 x 0,44 x 0,35 m  
 Vol 0,0678 m<sup>3</sup>  
 Gross weight 5 Kg Net weight 4 Kg



4878



**Finishes**  
 ● **18/** \_\_ Graphite (Adapta RF9913WX)  
 ● **58/** \_\_ Cream (RAL 7044)  
 ● **93/** \_\_ White (RAL 9016)  
**Finish customization**  
 (Available options: Vibia colour palette. Minimum quantity 10 units. Price + 10%)

**LED Colour Temperature**  
**Static White**  
 /1 \_ 2700 K - 2207 lm  
 /3 \_ 3500 K - 2304 lm  
**Tunable White**  
 /8 \_ (2200 K - 4000 K) 1901 lm - 2461 lm  
 CRI >90


**Control**  
**4878** \_\_ / \_\_  
 \_\_ / \_ **A** Static White + Push; 1-10V; DALI-2  
 \_\_ / \_ **Z** Static White + Casambi  
 \_\_ / \_ **81** Tunable White + DALI-2 DT8  
 \_\_ / \_ **8Z** Tunable White + Casambi

**Materials**  
 Diffuser: PC- Polycarbonate.  
 Main Body: Aluminum.  
 Inner structure: Oak wood.

**Light Source and electronics**  
 1 x LED PLATE 26,5 W 700 mA  
 Constant Current 350 mA  
 110-240V 50/60Hz

**Packaging**  
 1 Box 0,79 x 0,79 x 0,59 m  
 Vol 0,3682 m<sup>3</sup>  
 Gross weight 16 Kg Net weight 14 Kg  
 LED IP20 CE UK ENE Bi-volt

4880



**Finishes**  
 ● **18/** \_\_ Graphite (Adapta RF9913WX)  
 ● **58/** \_\_ Cream (RAL 7044)  
 ● **93/** \_\_ White (RAL 9016)  
**Finish customization**  
 (Available options: Vibia colour palette. Minimum quantity 10 units. Price + 10%)

**LED Colour Temperature**  
**Static White**  
 /1 \_ 2700 K - 2207 lm  
 /3 \_ 3500 K - 2304 lm  
**Tunable White**  
 /8 \_ (2200 K - 4000 K) 1901 lm - 2461 lm  
 CRI >90

**Control**  
**4880** \_\_ / \_\_  
 \_\_ / \_ **A** Static White + Push; 1-10V; DALI-2  
 \_\_ / \_ **Z** Static White + Casambi  
 \_\_ / \_ **81** Tunable White + DALI-2 DT8  
 \_\_ / \_ **8Z** Tunable White + Casambi

**Materials**  
 Diffuser: PC- Polycarbonate.  
 Main Body: Aluminum.  
 Inner structure: Oak wood.

**Light Source and electronics**  
 1 x LED PLATE 26,5 W 700 mA  
 Constant Current 350 mA  
 110-240V 50/60Hz

**Packaging**  
 1 Box 0,79 x 0,79 x 0,59 m  
 Vol 0,3682 m<sup>3</sup>  
 Gross weight 16 Kg Net weight 14 Kg  
 LED IP20 CE UK ENE Bi-volt

