

Tempo

Design by Lievore, Altherr

The Tempo collection reclaims our collective memory of light, distilling lighting archetypes to their most basic forms. Vibia presents three designs in two sizes: the disc, the diamond and the milk glass oval - all inspired by the interplay of opacity, translucence and transparency.

Wall



5756 5757

122,5 x 80 cm



5758 5759

116,5 x 80 cm



5760 5761

120 x 80 cm



5762 5763

42,5 x 140 cm




5764 5765

36,5 x 140 cm



5766 5767

40 x 140 cm




Ref.
5757, 5759, 5761, 5763, 5765, 5767.
Recessed dimmable driver.



Ref.
5756, 5758, 5760, 5762, 5764, 5766.
Push dimmer on the cable.
With plug.

5756



- Finishes
- 18/ __ Graphite (ADAPTA RF9913WX)
 - 37/ __ Terra Red (NCS S 4040-Y70R)
 - 58/ __ Cream (RAL 7044)
 - 62/ __ Green (NCS S 3010-G20Y)

LED Colour Temperature
 /1 _ 2700 K - 415 lm
 E
 CRI >90

Control
 5756 __ / 15 Push

Materials
 Diffuser: Blown-glass.
 LED support: Aluminum.
 Structures: Steel.
 Shade: Aluminum.


Light Source and electronics
 1 x LED 4 W 350 mA
 Constant Current 350 mA
 220~240V 50/60Hz

Packaging
 2 Boxes
 Total Vol 0,082 m³
 Gross weight 4,3 Kg Net weight 2,5 Kg

Notes
 Push dimmer on the cable. With plug (4 m)



5757



- Finishes
- 18/ __ Graphite (ADAPTA RF9913WX)
 - 37/ __ Terra Red (NCS S 4040-Y70R)
 - 58/ __ Cream (RAL 7044)
 - 62/ __ Green (NCS S 3010-G20Y)

LED Colour Temperature
 /1 _ 2700 K - 415 lm
 E
 CRI >90

Control
 5757 __ / __
 __ / _ 1 DALI-2
 __ / _ B Push; 1-10V
 __ / _ Z Casambi

Materials
 Diffuser: Blown-glass.
 LED support: Aluminum.
 Structures: Steel.
 Shade: Aluminum.


Light Source and electronics
 1 x LED 4 W 350 mA
 Constant Current 350 mA
 220~240V 50/60Hz

Packaging
 2 Boxes
 Total Vol 0,082 m³
 Gross weight 4,3 Kg Net weight 2,5 Kg

Notes
 Recessed dimmable driver (2,5 m)



5758



- Finishes
- 18/ __ Graphite (ADAPTA RF9913WX)
 - 37/ __ Terra Red (NCS S 4040-Y70R)
 - 58/ __ Cream (RAL 7044)
 - 62/ __ Green (NCS S 3010-G20Y)

LED Colour Temperature
 /1 _ 2700 K - 415 lm
 E
 CRI >90

Control
 5758 __ / 15 Push

Materials
 Diffuser: Blown-glass.
 LED support: Aluminum.
 Structures: Steel.


Light Source and electronics
 1 x LED 4 W 350 mA
 Constant Current 350 mA
 220~240V 50/60Hz

Packaging
 2 Boxes
 Total Vol 0,088 m³
 Gross weight 3,5 Kg Net weight 1,7 Kg

Notes
 Push dimmer on the cable. With plug (4 m).



5759



- Finishes**
- **18/** __ Graphite (ADAPTA RF9913WX)
 - **37/** __ Terra Red (NCS S 4040-Y70R)
 - **58/** __ Cream (RAL 7044)
 - **62/** __ Green (NCS S 3010-G20Y)

LED Colour Temperature
/1_ 2700 K - 415 lm
E →
CRI >90

Control
5759 __ / __
__ / __ 1 DALI-2
__ / __ B Push; 1-10V
__ / __ Z Casambi


Materials
Diffuser: Blown-glass.
LED support: Aluminum.
Structures: Steel.

Packaging
2 Boxes
Total Vol 0,088 m³
Gross weight 3,5 Kg Net weight 1,7 Kg

Light Source and electronics
1 x LED 4 W 350 mA
Constant Current 350 mA
220-240V 50/60Hz

Notes
Recessed dimmable driver (2,5 m)
LED IP20 CE UK EAC Ø 7,5 cm

5760



- Finishes**
- **18/** __ Graphite (ADAPTA RF9913WX)
 - **37/** __ Terra Red (NCS S 4040-Y70R)
 - **58/** __ Cream (RAL 7044)
 - **62/** __ Green (NCS S 3010-G20Y)

LED Colour Temperature
/1_ 2700 K - 415 lm
E →
CRI >90

Control
5760 __ / 15 Push


Materials
Diffuser: Blown-glass.
LED support: Aluminum.
Structures: Steel.

Packaging
2 Boxes
Total Vol 0,088 m³
Gross weight 3,7 Kg Net weight 1,9 Kg

Light Source and electronics
1 x LED 4 W 350 mA
Constant Current 350 mA
220-240V 50/60Hz

Notes
Push dimmer on the cable. With plug (4 m)
LED IP20 CE UK EAC Dimmer

5761



- Finishes**
- **18/** __ Graphite (ADAPTA RF9913WX)
 - **37/** __ Terra Red (NCS S 4040-Y70R)
 - **58/** __ Cream (RAL 7044)
 - **62/** __ Green (NCS S 3010-G20Y)

LED Colour Temperature
/1_ 2700 K - 415 lm
E →
CRI >90

Control
5761 __ / __
__ / __ 1 DALI-2
__ / __ B Push; 1-10V
__ / __ Z Casambi


Materials
Diffuser: Blown-glass.
LED support: Aluminum.
Structures: Steel.

Packaging
2 Boxes
Total Vol 0,088 m³
Gross weight 3,7 Kg Net weight 1,9 Kg

Light Source and electronics
1 x LED 4 W 350 mA
Constant Current 350 mA
220-240V 50/60Hz

Notes
Recessed dimmable driver (2,5 m)
LED IP20 CE UK EAC Ø 7,5 cm

5762



Finishes

- 18/ _ _ Graphite (ADAPTA RF9913WX)
- 37/ _ _ Terra Red (NCS S 4040-Y70R)
- 58/ _ _ Cream (RAL 7044)
- 62/ _ _ Green (NCS S 3010-G20Y)

LED Colour Temperature

/1 _ 2700 K - 415 lm

 CRI >90

Control

5762 _ _ / 15 Push

Materials

Diffuser: Blown-glass.
 LED support: Aluminum.
 Structures: Steel.
 Shade: Aluminum.

Light Source and electronics

1 x LED 4 W 350 mA
 Constant Current 350 mA
 220-240V 50/60Hz

Packaging


2 Boxes
 Total Vol 0,088 m³
 Gross weight 3,2 Kg Net weight 2 Kg

Notes

Push dimmer on the cable. With plug (4 m)



5763



Finishes

- 18/ _ _ Graphite (ADAPTA RF9913WX)
- 37/ _ _ Terra Red (NCS S 4040-Y70R)
- 58/ _ _ Cream (RAL 7044)
- 62/ _ _ Green (NCS S 3010-G20Y)

LED Colour Temperature

/1 _ 2700 K - 415 lm

 CRI >90

Control

5763 _ _ / _ _
 _ _ / _ 1 DALI-2
 _ _ / _ B Push; 1-10V
 _ _ / _ Z Casambi

Materials

Diffuser: Blown-glass.
 LED support: Aluminum.
 Structures: Steel.
 Shade: Aluminum.

Light Source and electronics

1 x LED 4 W 350 mA
 Constant Current 350 mA
 220-240V 50/60Hz

Packaging


2 Boxes
 Total Vol 0,088 m³
 Gross weight 3,2 Kg Net weight 2 Kg

Notes

Recessed dimmable driver (2,5 m)



5764



Finishes

- 18/ _ _ Graphite (ADAPTA RF9913WX)
- 37/ _ _ Terra Red (NCS S 4040-Y70R)
- 58/ _ _ Cream (RAL 7044)
- 62/ _ _ Green (NCS S 3010-G20Y)

LED Colour Temperature

/1 _ 2700 K - 415 lm

 CRI >90

Control

5764 _ _ / 15 Push

Materials

Diffuser: Blown-glass.
 LED support: Aluminum.
 Structures: Steel.

Light Source and electronics

1 x LED 4 W 350 mA
 Constant Current 350 mA
 220-240V 50/60Hz

Packaging


2 Boxes
 Total Vol 0,088 m³
 Gross weight 2,45 Kg Net weight 1,25 Kg

Notes

Push dimmer on the cable. With plug (4 m)




5765



Finishes ● 18/ __ Graphite (ADAPTA RF9913WX) ● 37/ __ Terra Red (NCS S 4040-Y70R) ● 58/ __ Cream (RAL 7044) ● 62/ __ Green (NCS S 3010-G20Y)	LED Colour Temperature /1_ 2700 K - 415 lm E CRI >90	Control 5765 __ / __ __ / __ 1 DALI-2 __ / __ B Push; 1-10V __ / __ Z Casambi
---	--	--

Materials Diffuser: Blown-glass. LED support: Aluminum. Structures: Steel. Light Source and electronics 1 x LED 4 W 350 mA Constant Current 350 mA 220-240V 50/60Hz	Packaging 2 Boxes Total Vol 0,088 m ³ Gross weight 2,45 Kg Net weight 1,25 Kg Notes Recessed dimmable driver (2,5 m) LED IP20 CE UK ENEC Ø 7,5 cm
--	---


5766



Finishes ● 18/ __ Graphite (ADAPTA RF9913WX) ● 37/ __ Terra Red (NCS S 4040-Y70R) ● 58/ __ Cream (RAL 7044) ● 62/ __ Green (NCS S 3010-G20Y)	LED Colour Temperature /1_ 2700 K - 415 lm E CRI >90	Control 5766 __ / 15 Push
---	--	-------------------------------------

Materials Diffuser: Blown-glass. LED support: Aluminum. Structures: Steel. Light Source and electronics 1 x LED 4 W 350 mA Constant Current 350 mA 220-240V 50/60Hz	Packaging 2 Boxes Total Vol 0,088 m ³ Gross weight 2,65 Kg Net weight 1,45 Kg Notes Push dimmer on the cable. With plug (4 m) LED IP20 CE UK ENEC Dimmer
--	---

5767



Finishes ● 18/ __ Graphite (ADAPTA RF9913WX) ● 37/ __ Terra Red (NCS S 4040-Y70R) ● 58/ __ Cream (RAL 7044) ● 62/ __ Green (NCS S 3010-G20Y)	LED Colour Temperature /1_ 2700 K - 415 lm E CRI >90	Control 5767 __ / __ __ / __ 1 DALI-2 __ / __ B Push; 1-10V __ / __ Z Casambi
---	--	--

Materials Diffuser: Blown-glass. LED support: Aluminum. Structures: Steel. Light Source and electronics 1 x LED 4 W 350 mA Constant Current 350 mA 220-240V 50/60Hz	Packaging 2 Boxes Total Vol 0,088 m ³ Gross weight 2,65 Kg Net weight 1,45 Kg Notes Recessed dimmable driver (2,5 cm) LED IP20 CE UK ENEC Ø 7,5 cm
--	--

