

Table



5965
35 x Ø 30 x 16 cm



5970
29 x 17 x 30 cm




5972
11 x 30 cm

Bolt-down



5965



- Finishes**
- 13/ __ Off-White (NCS S 1000-N)
 - 47/ __ Green L1 (NCS S 4005-G80Y)

LED Colour Temperature
/1 _ 2700 K - 682 lm
F >

CRI >90

Control
5965 __ /15 Push
(with or without memory)

Materials
Shade: Aluminum.
Diffuser: PC- Polycarbonate.
Structures: Steel.


Light Source and electronics
1 x LED PLATE 7W 400mA
Constant Voltage 24V
110-240V 50/60Hz

Packaging
1 Box 0,50 x 0,50 x 0,7 m
Vol 0,0018 m³
Gross weight 4 Kg Net weight 3,11 Kg

Notes
Electric cable 2 m

LED IP20 CE UK ENEC Dimmer Bi-volt

5970



- Finishes**
- 11/ __ Black (NCS S 8500-N)
 - 37/ __ Terra Red (NCS S 4040-Y70R)
 - 47/ __ Green L1 (NCS S 4005-G80Y)

LED Colour Temperature
/1 _ 2700 K - 682 lm
F >

CRI >90

Control
5970 __ /15 Push
(with or without memory)

Materials
Shade: Aluminum.
Diffuser: PC- Polycarbonate.
Structures: Steel.


Light Source and electronics
1 x LED PLATE 7W 400mA
Constant Voltage 24V
110-240V 50/60Hz

Packaging
1 Box 0,20 x 0,40 x 0,07 m
Vol 0,0072 m³
Gross weight 4 Kg Net weight 3,11 Kg

Notes
Electric cable 2 m

LED IP20 CE UK ENEC Dimmer Bi-volt

5972



- Finishes**
- 11/ __ Black (NCS S 8500-N)
 - 37/ __ Terra Red (NCS S 4040-Y70R)
 - 47/ __ Green L1 (NCS S 4005-G80Y)

LED Colour Temperature
/1 _ 2700 K - 682 lm
F >

CRI >90

Control
5972 __ /15 Push
(with or without memory)

Materials
Shade: Aluminum.
Diffuser: PC- Polycarbonate.
Structures: Steel.

Light Source and electronics
1 x LED PLATE 7W 400mA
Constant Voltage 24V
110-240V 50/60Hz

Packaging
1 Box 0,15 x 0,13 x 0,36 m
Vol 0,00702 m³
Gross weight 0,9 Kg Net weight 0,6 Kg

Notes
Electric cable 2 m

LED IP20 CE UK ENEC Dimmer