

---

Floor



**7480**  
Ø 45 x 178 cm



**7485**  
Ø 45 x 170 cm



**7487**  
Ø 65 x 195 cm



**7490**  
Ø 45 x 55 cm




**7492**  
Ø 65 x 51 cm



**7494**  
Ø 65 x 62 cm

7480



**Finishes**  
 ● 24/ \_ \_ Beige M1  
 (NCS S 2005-Y50R)

**LED Colour Temperature**  
 /1\_ 2700 K - 4740 lm  
 E  
 CRI >90

**Control**  
 7480 \_ \_ / \_ \_

\_ \_ / \_ 5 Push  
 \_ \_ / \_ Y ProtoPixel\*  
 \_ \_ / \_ Z Casambi

**Materials**

Fabric shade: PES FR.  
 Interior diffuser: PE- Polyethylene.  
 Botom diffuser: PMMA.  
 Diffuser ring and support: ABS.  
 Stem: Iron.  
 Floor base: Zinc Alloy.

**Light Source and electronics**  
 6 x LED 5,9W 350 mA  
 Constant Voltage 42V 1,43mA  
 110-240V 50/60Hz

**Packaging**

2 Boxes  
 Box 1: 0,54 x 0,54 x 0,41 m  
 Box 2: 1,71 x 0,38 x 0,36 m  
 Total Vol. 0,4311 m<sup>3</sup>  
 Gross weight 21,9 Kg Net weight 11,3 Kg

**Notes**


ProtoPixel products are compatible with all other DALI-2 products via a designated gateway (please consult us).

\*Available from January 2025.

Electric cable 2,5 m.



7485



**Finishes**  
 ● 24/ \_ \_ Beige M1  
 (NCS S 2005-Y50R)

**LED Colour Temperature**  
 /1\_ 2700 K - 4740 lm  
 E  
 CRI >90

**Control**  
 7485 \_ \_ / \_ \_

\_ \_ / \_ 5 Push  
 \_ \_ / \_ Y ProtoPixel\*  
 \_ \_ / \_ Z Casambi

**Materials**

Fabric shade: PES FR.  
 Interior diffuser: PE- Polyethylene.  
 Botom diffuser: PMMA.  
 Diffuser ring and support: ABS.  
 Stem: Iron.  
 Floor base: Zinc Alloy.

**Light Source and electronics**  
 6 x LED 5,9W 350 mA  
 Constant Voltage 42V 1,43mA  
 110-240V 50/60Hz

**Packaging**

2 Boxes  
 Box 1: 0,54 x 0,54 x 0,41 m  
 Box 2: 1,71 x 0,38 x 0,36 m  
 Total Vol. 0,353 m<sup>3</sup>  
 Gross weight 21,5 Kg Net weight 10,8 Kg

**Notes**


ProtoPixel products are compatible with all other DALI-2 products via a designated gateway (please consult us).

\*Available from January 2025.

Electric cable 2,5 m.



7487



**Finishes**  
 ● 24/ \_ \_ Beige M1  
 (NCS S 2005-Y50R)

**LED Colour Temperature**  
 /1\_ 2700 K - 4740 lm  
 E  
 CRI >90

**Control**  
 7487 \_ \_ / \_ \_

\_ \_ / \_ 5 Push  
 \_ \_ / \_ Y ProtoPixel\*  
 \_ \_ / \_ Z Casambi

**Materials**

Fabric shade: PES FR.  
 Interior diffuser: PE- Polyethylene.  
 Botom diffuser: PMMA.  
 Diffuser ring and support: ABS.  
 Stem: Iron.  
 Floor base: Zinc Alloy.

**Light Source and electronics**  
 6 x LED 5,9W 350 mA  
 Constant Voltage 42V 1,43 mA  
 110-240V 50/60Hz

**Packaging**

2 Boxes  
 Box 1: 0,78 x 0,78 x 0,59 m  
 Box 2: 1,93 x 0,45 x 0,46 m  
 Total Vol. 0,7649 m<sup>3</sup>  
 Gross weight 30 Kg Net weight 18,5 Kg

























**Notes**

ProtoPixel products are compatible with all other DALI-2 products via a designated gateway (please consult us).

\*Available from January 2025.

Electric cable 2,5 m



<p><b>7490</b></p> 	<p><b>Finishes</b></p> <p>● <b>24/</b> __ Beige M1 (NCS S 2005-Y50R)</p>	<p><b>LED Colour Temperature</b></p> <p><b>/1</b> _ 2700 K - 4740 lm</p> <p></p> <p>CRI &gt;90</p>	<p><b>Control</b></p> <p><b>7490</b> __ / __</p> <hr/> <p>__ / _ <b>5</b> Push</p> <p>__ / _ <b>Z</b> Casambi</p> <hr/> <p><b>Materials</b></p> <p>Fabric shade: PES FR. Interior diffuser: PE- Polyethylene. Botom diffuser: PMMA. Diffuser ring and support: ABS.</p> <p><b>Light Source and electronics</b></p> <p>6 x LED 5,9 W 350 mA Constant Voltage 42V 1,43 mA 110-240V 50/60Hz</p> <hr/> <p><b>Packaging</b></p> <p>1 Box 0,65 x 0,55 x 0,55 m Vol 0,196 m<sup>3</sup> Gross Weight 5,4 Kg Net Weight 3,3 Kg</p> <p><b>Notes</b></p> <p>Push on the top of the luminaire. Electric cable 2,5 m</p> <p>     </p>
<p><b>7492</b></p> 	<p><b>Finishes</b></p> <p>● <b>24/</b> __ Beige M1 (NCS S 2005-Y50R)</p>	<p><b>LED Colour Temperature</b></p> <p><b>/1</b> _ 2700 K - 4740 lm</p> <p></p> <p>CRI &gt;90</p>	<p><b>Control</b></p> <p><b>7492</b> __ / __</p> <hr/> <p>__ / _ <b>5</b> Push</p> <p>__ / _ <b>Z</b> Casambi</p> <hr/> <p><b>Materials</b></p> <p>Fabric shade: PES FR. Interior diffuser: PE- Polyethylene. Botom diffuser: PMMA. Diffuser ring and support: ABS.</p> <p><b>Light Source and electronics</b></p> <p>6 x LED 5,9 W 350 mA Constant Voltage 42V 1,43 mA 110-240V 50/60Hz</p> <hr/> <p><b>Packaging</b></p> <p>1 Box 0,78 x 0,78 x 0,59 m Vol 0,358 m<sup>3</sup> Gross Weight 7,3 Kg Net Weight 4,5 Kg</p> <p><b>Notes</b></p> <p>Push on the top of the luminaire. Electric cable 2,5 m.</p> <p>     </p>
<p><b>7494</b></p> 	<p><b>Finishes</b></p> <p>● <b>24/</b> __ Beige M1 (NCS S 2005-Y50R)</p>	<p><b>LED Colour Temperature</b></p> <p><b>/1</b> _ 2700 K - 4740 lm</p> <p></p> <p>CRI &gt;90</p>	<p><b>Control</b></p> <p><b>7494</b> __ / __</p> <hr/> <p>__ / _ <b>5</b> Push</p> <p>__ / _ <b>Z</b> Casambi</p> <hr/> <p><b>Materials</b></p> <p>Fabric shade: PES FR. Interior diffuser: PE- Polyethylene. Botom diffuser: PMMA. Diffuser ring and support: ABS.</p> <p><b>Light Source and electronics</b></p> <p>6 x LED 5,9 W 350 mA Constant Voltage 42V 1,43 mA 110-240V 50/60Hz</p> <hr/> <p><b>Packaging</b></p> <p>1 Box 0,80 x 0,80 x 0,75 m Vol 0,48 m<sup>3</sup> Gross Weight 9,3 Kg Net Weight 5,9 Kg</p> <p><b>Notes</b></p> <p>Push on the top of the luminaire. Electric cable 2,5 m.</p> <p>     </p>



