

DOT R

Omar Carraglia - Davide Groppi / 2015



A tool to light.

A luminaire designed for use with state-of-the-art LED modules to offer superior performance and a wide range of light beams.

Elemento di luce.

Un apparecchio illuminante progettato per utilizzare moduli a LED in grado di fornire prestazioni superiori ed un'ampia gamma di fasci luminosi.


DOT R

Omar Carraglia - Davide Groppi / 2015

Recessed / Direct / Indoor

| | | | |
|-----------------|-----------------------|-----------------------|-------------------------------------|
| Material | Metal | | |
| Finish | .03 Matt White | .04 Matt Black | .49 Matt Black/Polished Gold |

Note Recessed luminaire. Adjustable in all directions. Plasterboard hole: 40x40 mm. Minimum space for recessed installation: 40 mm. *Apparecchio illuminante da incasso. Orientabile in tutte le direzioni. Foro del cartongesso: 40x40 mm. Spazio minimo per incasso: 40 mm.*




DOT R

13W
Max 350mA DC
2700K / 3000K
CRI >97
Driver not included



Matt White - 2700K
Matt White - 3000K
Matt Black - 2700K
Matt Black - 3000K
Matt Black/Polished Gold - 2700K
Matt Black/Polished Gold - 3000K

1A4770300.27.20
1A4770300.30.20
1A4770400.27.20
1A4770400.30.20
1A4774900.27.20
1A4774900.30.20



DOT R 51

Max 10W - GU10
100-240V - 50/60Hz
ON/OFF
Bulb not included



Matt White - ON/OFF
Matt Black - ON/OFF
Matt Black/Polished Gold - ON/OFF

1A3700300.00.00
1A3700400.00.00
1A3704900.00.00


The sizes are expressed in millimeters.

Omar Carraglia - Davide Groppi / 2015


DOT R

Compulsory accessories / Accessori obbligatori


Drivers / Alimentatori



| Driver / Alimentatore | | | | Not included |
|-----------------------|--------------------------|-------|---------------|--------------|
| 220-240V(100-127V) | 350mA/17W(15W)/IP20/DALI | DOT R | 1Z0241180.350 | |



| Driver / Alimentatore | | | | Not included |
|-----------------------|----------------------------------|-------|---------------|--------------|
| 220-240V(100-127V) | 350mA/18W(15W)/IP20/PUSH - 1-10V | DOT R | 1Z0240870.350 | |



| Driver / Alimentatore | | | | Not included |
|-----------------------|---------------------------|-------|---------------|--------------|
| 220-240V | 350mA/17W/IP20/TRIAC/IGBT | DOT R | 1Z0240850.350 | |


Other accessories / Altri accessori




| Lens / Lente | | | Not included |
|--------------|--------------------------|-------|-----------------|
| Beam - 14° | 2700K - CRI >97 - 983lm | DOT R | 1A3090000.00.00 |
| | 3000K - CRI >97 - 1038lm | | |
| Beam - 24° | 2700K - CRI >97 - 943lm | DOT R | 1A3100000.00.00 |
| | 3000K - CRI >97 - 996lm | | |
| Beam - 36° | 2700K - CRI >97 - 955lm | DOT R | 1A3110000.00.00 |
| | 3000K - CRI >97 - 1005lm | | |
| Beam - 50° | 2700K - CRI >97 - 965lm | DOT R | 1A3120000.00.00 |
| | 3000K - CRI >97 - 1016lm | | |

Optional accessories / Accessori opzionali


Other accessories / Altri accessori




| | | | |
|--|-------|-----------------|--------------|
| Accessory holder + Honeycomb louvre / Porta accessori + Frangiluce nido d'ape | | | Not included |
| | DOT R | 1X0080400.01.00 | |




| | | | |
|---|---------------------------------|-------|-----------------|
| Elliptical filter / Filtro ellittico | | | Not included |
| Standard | Compulsory with 1X0080400.01.00 | DOT R | 1X0080000.02.00 |



| | | | |
|---------------------------------|---------------------------------|-------|-----------------|
| Blue filter / Filtro blu | | | Not included |
| Standard | Compulsory with 1X0080400.01.00 | DOT R | 1X0080000.03.00 |



| | | | |
|----------------------------------|---------------------------------|-------|-----------------|
| Red filter / Filtro rosso | | | Not included |
| Standard | Compulsory with 1X0080400.01.00 | DOT R | 1X0080000.04.00 |



| | | | |
|--------------------------------------|---------------------------------|-------|-----------------|
| Yellow filter / Filtro giallo | | | Not included |
| Standard | Compulsory with 1X0080400.01.00 | DOT R | 1X0080000.05.00 |

Optional accessories / Accessori opzionali

Bulbs / Lampadine



| | | | |
|---------------------------|--|----------|--------------|
| LED - GU10 - PAR16 | | | Not included |
| | 220-240V - 5,5W - 25° 3000K - 375lm - CRI >97 Energy Efficiency G - Dimmable | DOT R 51 | 1Y0330500 |




| | | | |
|--------------------------------|--|----------|--------------|
| LED SORAA - GU10 - MR16 | | | Not included |
| | 230V - 7,5W - 10° 2700K - 390lm - CRI >95 Energy Efficiency G - Dimmable | DOT R 51 | 1Y1580210 |




| | | | |
|--------------------------------|--|----------|--------------|
| LED SORAA - GU10 - MR16 | | | Not included |
| | 230V - 7,5W - 10° 3000K - 410lm - CRI >95 Energy Efficiency G - Dimmable | DOT R 51 | 1Y1580010 |


Other accessories / Altri accessori



| | | | |
|------------------|-------------------------|----------|--------------|
| Darklight | | | Not included |
| | LED SORAA - GU10 - MR16 | DOT R 51 | 1Y1580040 |



| | | | |
|--|-------------------------|----------|--------------|
| 25° beam filter / Filtro fascio 25° | | | Not included |
| | LED SORAA - GU10 - MR16 | DOT R 51 | 1Y1580020 |



| | | | |
|--|-------------------------|----------|--------------|
| 36° beam filter / Filtro fascio 36° | | | Not included |
| | LED SORAA - GU10 - MR16 | DOT R 51 | 1Y1580030 |