Febe Suspension 2700K - Dove grey


Ernesto Gismondi



DESCRIPTION

Febe boasts an understated shape despite being superior in performance, giving the light it emits the utmost importance, while almost disappearing from view in its surroundings owing to its simplicity and minimal thickness.





LUMINAIRE

- Watt: 30W
- Voltage: 220-240V
- Delivered lumen output: 2182lm
- CCT: **2700K**
- Efficiency: 85%
- Efficacy: 72.73lm/W
- CRI: 90
- Dimmable Typology: Push


FEATURES

- Product Code: 0242W20A
- Colour: Dove grey
- Installation: Suspension
- Material: Methacrylare, polycarbonate
- Series: Design Collection
- Environment: Indoor
- design by: Ernesto Gismondi

DIMENSIONS

- Width: 76 mm
- Diameter: 610 mm
- Base Width: **44 mm**
- Base Diameter: 270 mm
- Max Height from ceiling: 2000 mm
- Glow Wire Test: **750°**

- Category: Led
- Number: **4**
- Watt: 6.20W
- Delivered lumen output: 630lm
- Color temperature (K): 2700K
- CRI: 90
- Color Tolerance: MacAdam 3SDCM
- Efficacy: 102lm/W
- Service Life: **50000-L70**





Febe Suspension 2700K - White


Ernesto Gismondi



DESCRIPTION

Febe boasts an understated shape despite being superior in performance, giving the light it emits the utmost importance, while almost disappearing from view in its surroundings owing to its simplicity and minimal thickness.





LUMINAIRE

- Watt: 30W
- Voltage: 220-240V
- Delivered lumen output: 2182lm
- CCT: **2700K**
- Efficiency: **85%**
- Efficacy: 72.73lm/W
- CRI: 90
- Dimmable Typology: Push


FEATURES

- Product Code: 0242W00A
- Colour: White
- Installation: Suspension
- Material: Methacrylare, polycarbonate
- Series: Design Collection
- Environment: Indoor
- design by: Ernesto Gismondi

DIMENSIONS

- Width: 76 mm
- Diameter: 610 mm
- Base Width: **44 mm**
- Base Diameter: 270 mm
- Max Height from ceiling: 2000 mm
- Glow Wire Test: **750°**

- Category: Led
- Number: **4**
- Watt: 6.20W
- Delivered lumen output: 630lm
- Color temperature (K): 2700K
- CRI: 90
- Color Tolerance: MacAdam 3SDCM
- Efficacy: 102lm/W
- Service Life: **50000-L70**





Febe Suspension 3000K - Dove grey


Ernesto Gismondi



DESCRIPTION

Febe boasts an understated shape despite being superior in performance, giving the light it emits the utmost importance, while almost disappearing from view in its surroundings owing to its simplicity and minimal thickness.





LUMINAIRE

- Watt: 30W
- Voltage: 220-240V
- Delivered lumen output: 2260lm
- CCT: **3000K**
- Efficiency: **85%**
- Efficacy: 75.33lm/W
- CRI: 90
- Dimmable Typology: Push

FEATURES

- Product Code: 0242020A
- Colour: Dove grey
- Installation: Suspension
- Material: Methacrylare, polycarbonate
- Series: Design Collection
- Environment: Indoor
- design by: Ernesto Gismondi

DIMENSIONS

- Width: 76 mm
- Diameter: 610 mm
- Base Width: **44 mm**
- Base Diameter: 270 mm
- Max Height from ceiling: 2000 mm
- Glow Wire Test: **750°**

- Category: Led
- Number: **4**
- Watt: 6.20W
- Delivered lumen output: 653lm
- Color temperature (K): **3000K**
- CRI: 90
- Color Tolerance: MacAdam 3SDCM
- Efficacy: 105lm/W
- Service Life: **50000-L70**



Febe Suspension 3000K - White


Ernesto Gismondi



DESCRIPTION

Febe boasts an understated shape despite being superior in performance, giving the light it emits the utmost importance, while almost disappearing from view in its surroundings owing to its simplicity and minimal thickness.





LUMINAIRE

- Watt: 30W
- Voltage: 220-240V
- Delivered lumen output: 2260lm
- CCT: **3000K**
- Efficiency: **85%**
- Efficacy: 75.33lm/W
- CRI: 90
- Dimmable Typology: Push

FEATURES

- Product Code: 0242000A
- Colour: White
- Installation: Suspension
- Material: Methacrylare, polycarbonate
- Series: Design Collection
- Environment: Indoor
- design by: Ernesto Gismondi

DIMENSIONS

- Width: 76 mm
- Diameter: 610 mm
- Base Width: **44 mm**
- Base Diameter: 270 mm
- Max Height from ceiling: 2000 mm
- Glow Wire Test: **750°**

- Category: Led
- Number: 4
- Watt: 6.20W
- Delivered lumen output: 653Im
- Color temperature (K): **3000K**
- CRI: 90
- Color Tolerance: MacAdam 3SDCM
- Efficacy: 105lm/W
- Service Life: 50000-L70

