
Ilio 10 Special Edition - 2700K - App Compatible

Ernesto Gismondi







LUMINAIRE

- Watt: **45W**

- Voltage: 220-240V

- Delivered lumen output: 3332lm

- CCT: **2700K**- Efficiency: **87%**

Efficacy: 74.04lm/W

- CRI: **90**

Notes

DESCRIPTION

Artemide celebrates the 10th anniversary of Ilio with a special autographed and numbered version of 2000 pieces. Designed by Artemide's founder Ernesto Gismondi, Ilio is an essential and timeless element.

It is a synthesis of manufacturing and functional intelligences that is renewed thanks to a refined and sustainable shaded metal finish obtained with PVD technology.

This gradation of shades, ranging from warm to cold, gold to silver, interacts with its surroundings by gently reflecting the colours.

Ilio 10 special edition is not only an extremely highperforming and efficient lighting product, but also an iconic and unique object.

In fact, each piece of this limited edition is engraved with both Ernesto Gismondi's signature and serial number. The finish obtained with the PVD (Phisical Vapour Deposition) process is another demonstration of Artemide's attitude towards an increasingly sustainable design and production. Dynamic light management with Artemide App makes each author aware of their own light.

Ilio 10 Special Edition celebrates the past while projecting into the future.

FEATURES

- Product Code: 1640W00APP

Colour: Gold/SilverInstallation: Floor

Material: Aluminium, steelSeries: Design Collectiondesign by: Ernesto Gismondi

DIMENSIONS

Height: 1750 mm
Diameter: 90 mm
Base Length: 300 mm
Base Width: 300 mm
Impact Resistance: N.D.
Glow Wire Test: 750°

SOURCES INCLUDED



PRODUCT DATA SHEET

PRODUCT CODE: 1640W00APP

Category: LedNumber: 1Watt: 36.36W

Delivered lumen output: 3646lmColor temperature (K): 2700K

- CRI: **90**

- Color Tolerance: MacAdam 2SDCM

Efficacy: 100lm/WService Life: 50000-L70

Accessories



Device for switching and controlling Artemide App products. Max N.3 inputs for external push buttons. Max 1m distance. Mains power supply required. To be installed inside flush mounting boxes or junction boxes. DV1080APP

